



Aerobic Biological In-situ Remediation

Martin Slooijer

16th of July 2013



bioSoil

Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5



bioSoil

Contaminants

Hydrocarbons such as
Mineral oil, BTEX, PAH

- Free phase (mostly LNAPL (sometimes) DNAPL)
- Smearzone
- Hydrofobic
- Aerobic biodegradable



Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5



bioSoil

In-situ Treatment

Biological Remediation :
Optimalisation of environment in
the soil to stimulate natural
biodegradation



Soil = bioreactor

In-situ Treatment

Electrondonor
(C –source)

Mineral Oil
BTEX


CO_2

Electronacceptor
(respiration)

O_2

H_2O

Nutrients (Nitrogen, phosphate)



bioSoil

Content

1. Contaminants
2. Biological Degradation (Aerobic)
- 3. In-situ Remediation**
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5




bioSoil

In-situ Treatment


Aerobic Remediation

Groundwater circulation for distribution of nutriënts

Air injection for supply of oxygen



In-situ remediation



In-situ Bioreactor




bioSoil

In-situ Treatment

Important:

- Cyclic design
- Soil structure



Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5



bioSoil

Case 1: Quilicura Chile



bioSoil

Project description

- Soil and groundwater contamination with BTEX and Styrene
- Contamination has spread up to 16 m-gl
- The contamination covers an area of 1.5 ha.
- Groundwater table is at 10,5 m-gl
- Soil structure is very complex
- Location is still operational



bioSoil

Remediation approach

The unsaturated zone: ***Soil Vapour Extraction:***

- SVE filters 3-9,5 m-gl
- Biofilters for cleaning of Vapour


The saturated zone: ***Enhanced Biological Degradation***

- Extraction wells 16 m-gl
- Water treatment : bioreactors
- Infiltration wells 16 m-gl
- Airsparging lances 16 m-gl



bioSoil

Remediation approach



Project Results

Final verification, about 40 soil samples only two exceeding detection limit of the lab:

Parameter	Start	Objective Soil (mg/kg)	B26 (7,5-8,0 m- mv)	D16-15 (8,0-8,5 m- mv)
Benzene	22,0	0,3	<	<
Toluene	27,3	7	<	<
Ethylbenzene	341,3	5	<	0,06
Xylene	2.616,6	25	<	0,43
Styrene	20.000,0	25	0,38	5,3



bioSoil

Project Results Groundwater


Final verification in 2 events about 40 watersamples, only few samples exceeding the detection limit of the lab:

Parameter	Start	Objective Groundwater ($\mu\text{g/l}$)	Event I (Juli 2009)	Event II (November 2009)
Benzene	840	700	<	GAC911-112 (1,0 $\mu\text{g/l}$)
Toluene	51.100	10.000	<	<
Ethylbenze ne	46.800	10.000	<	GAC911-112 (0,39 $\mu\text{g/l}$)
Xylene	1.146.000	5,000	<	GAC911-112 (0,44 $\mu\text{g/l}$)
Styrene	32.100	5,000	<	<




bioSoil

Vapor extraction - Xylene - (ppm) (August 2004)




*bio*Soil

Vapor extraction - Xylene - (ppm) (March 2005)



bioSoil

Vapor extraction - Xylene - (ppm) (March 2006)



*bio*Soil


Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
- 5. Case 2**
6. Case 3
7. Case 4
8. Case 5



bioSoil

Case 2: Sao Paulo State, Brazil




Project description

- Historical contamination of soil and groundwater with various contaminants:
- Soil structure clay / silt / sand

Contaminant	max level ($\mu\text{g/l}$)	Objective
Benzene	5,100,000	5
Toluene	2,900	170
ethylbenzene	8,300	200
o-xylene	15,000	300
m- and p-xylene	25,000	300
1,3,5-trimethylbenzene	160	1,900
1,2-dichloroethane	34,000,000	10
dichloromethane	42,000	20

Remediation Design



Project Result

Well	Date	DCM	Benzene	1,2 DCA	Toluene
P21	Aug 09	20,320	7,143	159,910	4,593
	Dec 09	49	20	271	10
	March 10	223	72	1028	35
	July 10	< d	18	70	< d
	nov-10	NA	96	NA	44
	March 11	706	190	2,545	140
	oct-11	149	26	1,525	11
	sep-11	63	95	1,500	69
	Dec 11	108	272	376	250
	jun-12	19	11	500	6
	aug 12	< d		35	
	sep-12	< d	< d	19	< d
	Dec-12	< d	< d	< d	< d



*bio*Soil

Project Result

- After 2,5 years active remediation ended
- Currently monitoring of the result 1 year, still all results are good.



bioSoil

Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5



bioSoil

Case 3: Doesburg, the Netherlands



bioSoil

Project description


- Historical contamination of soil and groundwater with mineral oil and volatile organic carbons VOC
- Mainly Petrol and Diesel
- Free Phase LNAPL
- Soil structure sand and clay layer

T-Value	Soil (mg/kg)	Groundwater ($\mu\text{g/l}$)
TPH	500	325
Benzene	0.1	15
Toluene	13	500
Ethylbenzene	5	75
Xylene	2.5	35



bioSoil

Remediation design



Project Result

- After 3 years Groundwater < d
- Soil : 1.400 mg/kg Diesel.
- Remediation formally ended since no risk for spreading.



bioSoil

Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
- 7. Case 4**
8. Case 5




bioSoil

Aerobic Bioscreen




bioSoil

Location bioscreen and contamination



Monitoring effectiveness of the screen



Pictures



bioSoil

Result influx versus outflux


	bemonst. tijdstip	gem. influx		gem. outflux		Saneringsrendement op olie C6-40 + BTEXN influx versus outflux
		olie+BTEXN µg/l	af-/toename	olie+BTEXN µg/l	af-/toename	
Laag 1	06. - filters	T0	30.300	16.536	45%	
		T1	32.187	+6,2%	8.815	-46,7%
		T2	30.096	-6,5%	2.225	-74,8%
		T3	38.773	+28,8%	2.814	+26,5% ←
Laag 2	10. - filters	T0	1.168	6.384	-447%	
		T1	2.327	+99,3%	1.251	46%
		T2	2.421	+4,0%	1.136	53%
		T3	4.769	+97,0%	293	94% ←
Laag 3	13. - filters	T0	2.759	7.876	-185%	
		T1	2.648	-4,0%	953	64%
		T2	3.143	+18,7%	520	83%
		T3	3.867	+23,0%	35	99% ←
Laag 4	16. - filters	T0	2.949	1.812	39%	
		T1	1.698	-42,4%	157	91%
		T2	1.498	-11,8%	195	87%
		T3	2.731	+82,3%	289	89% ←
Laag 5	19. - filters	T0	1.878	12	99%	
		T1	308	-83,6%	3	99%
		T2	100	-67,5%	142	+5438,1% ←
		T3	1.580	+1474,7%	76	-46,5% ←




bioSoil

Concentration decrease behind the bioscreen


Gem. outflux olie C6-40+BTEXN Laag 1 (tot 6 m-mv)




Gem. outflux olie C6-40+BTEXN Laag 2 (tot 10 m-mv)



Gem. outflux olie C6-40+BTEXN Laag 3 (tot 13 m-mv)



Gem. outflux olie C6-40+BTEXN Laag 4 (tot 16 m-mv)



T0 = januari 2009

T1 = augustus 2009

T2 = december 2009

T3 = april 2010



Content

bioSoil

Content

1. Contaminants
2. Biological Degradation (Aerobic)
3. In-situ Remediation
4. Case 1
5. Case 2
6. Case 3
7. Case 4
8. Case 5



bioSoil

Case 5: Velp Hogeweg, the Netherlands



bioSoil

Project description


- Historical contamination of soil and groundwater with mineral oil and volatile organic carbons VOC
- Soil: 2,300 mg/kg TPH ; 710 mg/kg BTEX
- GW: 5,100 µg/l TPH ; 21,500 µg/l BTEX
- Soil structure sand
- Large groundwater plume

T-Value	Soil (mg/kg)	Groundwater (µg/l)
TPH	500	325
Benzene	0.1	15
Toluene	13	500
Ethylbenzene	5	75
Xylene	2.5	35



bioSoil

Remediation Design



Project Result

- After 2 years Groundwater << T- value just above detection limit.
- After 2.5 years Soil << T-value just above detection limit



bioSoil